

# DATASHEET

19" Wall Housing 6U, Fixed, 1-Part, RAL9005, Depth 450 mm



## General data

Steel sheet housing with welded frame, completely pre-assembled, self-ventilated

**NEW: Prepared for Plug & Play 2-fan unit Art.-No. 691656xx**

**NEW: Bottom with 4 x mounting point for leveling feet or castor set (please order separately)**

**NEW: Front door with metal hinges for increased stability**

Side walls removable, lockable, locks equal to door lock

Roof, bottom and rear wall with pre-punched openings for cable entry (250 x 70 mm)

Front-sided 2 x 19" profile rails, galvanised, depth-adjustable

Front door with latch locking and window made of certified safety glass (thickness 4 mm)

Internal earthing of all cabinet sections

Paint finish RAL9005, jet black

Protection degree IP20

Included in delivery: 1 x brush terminal, 1 x set of captive nuts (PU 20 pcs.), 2 x key

Delivery in transport packaging, from 30 kg / 12U on disposable pallet

## Allgemeine Daten

With front door	True
Type of ventilation	Passive
Surface finishing	powder coating
Number of cartons	1

This datasheet was created automatically on 27-03-2025 . Technical changes reserved.



# DATASHEET

## 19" Wall Housing 6U, Fixed, 1-Part, RAL9005, Depth 450 mm

With roof plate	True
Mounting level	Front side
With sidewall	True
Model	With permanent frame
With earthing	True
Number of doors	1
Type of profile rail	L-shaped

### General data

Modular spacing	482.6 mm (19 inch)
Material	steel
Degree of protection	IP20
Demountable	False

### Available variants

ArtNr.	Bezeichnung	Colour	Depth	Height	Max. Load	Number of height units	Width	RAL-Nummer
691706VTS.45	19" Wall Housing 6U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	330 mm	50 kg	6 U	600 mm	9005
691709VTS.45	19" Wall Housing 9U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	465 mm	50 kg	9 U	600 mm	9005
691712VTS.45	19" Wall Housing 12U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	600 mm	50 kg	12 U	600 mm	9005
691715VTS.45	19" Wall Housing 15U, Fixed, 1-Part, RAL9005, Depth 450 mm	black	450 mm	730 mm	50 kg	15 U	600 mm	9005

This datasheet was created automatically on 27-03-2025 . Technical changes reserved.

